Via Express Man No. EL89/8000920		- 1950 may		
FORM PTO-1390 DEPARTMENT OF COMMERCE PAT (REV 11-2000)	ATTORNEY'S DOCKET NO			
	851663.430USPC			
TRANSMITTAL LETTER TO THE UNITED STATES		U.S. APPLICATION NO (If known, see37 CFR 1.5)		
DESIGNATED/ELECTED OFFICE (DO/EO/US) CONCERNING A FILING UNDER 35 U.S.C. 371		Unknown 09/914171		
INTERNATIONAL APPLICATION NO.		PRIORITY DATE CLAIMED		
26 February 1999	PCT/SG99/00014	26 February 1999		
TITLE OF INVENTION		1		
	TERLACED/NON-INTERLACED FRAM	E DETERMINATION, REPEAT-FIELD		
IDENTIFICATION AND SCENE-CHA	ANGE DETECTION			
APPLICANT(S) FOR DO/EO/US	Human			
HUI, Yau Wei Lucas and GOH, Kwong Applicant herewith submits to the United St	ates Designated/Elected Office (DO/EO/US) the	following items and other information:		
	tems concerning a filing under 35 U.S.C. 371.			
	UENT submission of items concerning a filin	-		
3. Main This is an express request to beg items (5), (6), (9) and (21) indicates	in national examination procedures (35 U.S.C ted below.	. 371(f)). The submission must include		
4. The US has been elected by the	expiration of 19 months from the priority date	(Article 31).		
5. A copy of the International Appl	ication as filed (35 U.S.C. 371(c)(2)).			
a. is attached hereto (requ	ired only if not communicated by the Internati	ional Bureau).		
	d by the International Bureau.			
c. is not required, as the a	pplication was filed in the United States Recei	iving Office (RO/US).		
	of the International Application as filed (35 U			
a. is attached hereto				
h Dhac been previously sul	omitted under 35 U.S.C. 154(d)(4).			
		10 (25 H S C 271/ ₂)(2))		
	E International Application under PCT Article			
a. are attached hereto (rec	uired only if not communicated by the Interna	tional Bureau).		
	ed by the International Bureau.	•		
c. I have not been made; no	owever, the time limit for making such amendr	nents has NOT expired.		
d. A have not been made an	d will not be made.			
A translation of the amendments	to the claims under PCT Article 19 (35 U.S.C	2. 371(c)(3)).		
9. An oath or declaration of the inv	rentor(s) (35 U.S.C. 371(c)(4)).			
10. A English language translation of 36 (35 U.S.C. 371(c)(5)).	f the annexes to the International Preliminary	Examination Report under PCT Article		
Items 11 to 20 below concern document	(s) or information included:			
11. An Information Disclosure State	ment under 37 CFR 1.97 and 1.98.			
12. An assignment document for rec	ording. A separate cover sheet in compliance	with 37 CFR 3.28 and 3.31 is included.		
13. 🛛 A FIRST preliminary amendmer				
14. A SECOND or SUBSEQUENT	preliminary amendment.			
15. A substitute specification.	•			
	nd/or address letter			
1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1				
18. A second copy of the published international application under 35 U.S.C. 154(d)(4)				
19. A second copy of the English language translation of the international application under 35 U.S.C. 154(d)(4).				
20. Under items of information:				

C18 Rec'd PGT/PTO 2 4 AUG 2001

U.S. APPLICATION NO (I	known, see 37 GFP 1.5)	INTERNATIO	IONAL APPLICATION NO. ATTORNEY'S DOCKET NUMBER		IBER	
		PCT/SG99/	/00014 851663.430USPC			
21. The following fees are submitted:					CALCULATIONS	
Basic National Fee (37 CFR 1.492(a)(1)-(5)):						
Neither international preliminary examination fee (37 CFR 1.482) nor international search fee (37 CFR 1.445(a)(2)) paid to USPTO and International Search Report not prepared by the EPO or JPO\$1000.00						
International preliminary examination fee (37 CFR 1.482) not paid to USPTO but International Search Report prepared by the EPO or JPO						
International preliminary examination fee (37 CFR 1.482) not paid to USPTO but international search fee (37 CFR 1.445(a)(2)) paid to USPTO\$710.00						
International preliminary examination fee (37 CFR 1.482) paid to USPTO but all claims did not satisfy provisions of PCT Article 33(1)-(4)						
International preliminary examination fee (37 CFR 1.482) paid to USPTO and all claims satisfied provisions of PCT Article 33(1)-(4)						
	ENTER APPROI	PRIATE BA	SIC FEE AMO	UNT =	\$860.00	
Surcharge of \$130.00 for from the earliest claimed p	furnishing the oath or dec priority date (37 CFR 1.4	claration later 92(e)).	than 🗌 20 🛛	30 months	\$130.00	
Claims Claims	Number Filed	Nun	nber Extra	Rate		
Total Claims Independent Claims	10 - 20 = 2 - 3 =			x \$ 18.00	\$00.00	
Multiple dependent claim				x \$ 80.00 + \$270.00	\$00.00	
27 disple dependent claim		OF ABOVE	CALCULATIO		\$00.00 \$990.00	
Applicant claims sma	Il entity status. See 37 Cl	FR 1 27 The	fees indicated above	VA ore		
reduced by 1/2.	in charty status. See 37 Ci		Tees indicated abo	ve are	\$00.00	
			SUBTO	TAL =	\$990.00	
Processing fee of \$130.00 months from the earliest c	for furnishing the Englis laimed priority date (37 C	h translation l CFR 1.492(f)).	ater than 20	☐ 30 +	\$00.00	
		TOTA	L NATIONAL	FEE =	\$990.00	
Fee for recording the enclar accompanied by an appropriate appropriate the companies of the control of the cont	osed assignment (37 CFR priate cover sheet (37 CF)	R 3.28, 3.31).	\$40.00 per proper	ty +	\$00.00	
		TOTAL	FEES ENCLO	SED =	\$990.00	
- Secretary					Amount to be refunded:	
charged				L :		
	nount of <u>\$990.00</u> cover the					
b. Please charge my Deposit Account No. in the amount of \$_\text{to cover the above fees. A duplicate copy of this sheet is enclosed.}						
c.						
d. Fees are to be charged to a credit card. WARNING: Information on this form may become public. Credit card information should not be included on this form. Provide credit card information and authorization on PTO-2038.						
NOTE: Where an appropriate time limit under 37 CFR 1.494 or 1.495 has not been met, a petition to revive (37 CFR 1.137(a) or (b)) must be filed and granted to restore the application to pending spatus.						
i and granted to restore and approaction to perform spatials.						
SEND ALL CORRESPON	NDENCE TO:			h		
Robert Iannucci			SIGNATURE			
Seed Intellectual Property Law Group PLLC 701 5 th Avenue, Suite 6300 Robert Iannucci NAME						
Seattle, WA 98104-7092 United States of America 33.514						
United States of America (206) 622-4900 REGISTRATION NUMBER						

09/914171 510 Tac'd PCT/PTO 2 4 AUG 2001

EXPRESS MAIL NO. EL897866092US

1

PATENT COOPERATION TREATY

Int'l Application No.:

PCT/SG99/00014

Int'l Filing Date

26 February 1999

U.S. Application No.:

Not Yet Known

Inventor

HUI, Yau Wei Lucas and GOH, Kwong Huang

Title

METHOD AND APPARATUS FOR

INTERLACED/NON-INTERLACED FRAME

DETERMINATION, REPEAT-FIELD IDENTIFICATION AND

SCENE-CHANGE DETECTION

Docket No.

851663.430USPC

Date

24 August 2001

Box PCT

Assistant Commissioner for Patents

Washington, DC 20231-0001

PRELIMINARY AMENDMENT

Sir:

Applicants respectfully request entry of preliminary amendments in the aboveidentified United States National Phase patent application. Prior to examination on the merits, kindly enter the following amendment to the claims as follows:

In the Claims:

- 7. The method as claimed in claim 1, wherein said step of comparing first and second fields provides an output of the sum of a plurality of absolute pixel differences between respective said first and second fields, said absolute pixel differences exceeding a threshold value.
 - 8. A system for executing the method as claimed in claim 1.

REMARKS

The present amendment is made in order to place the claims in conformance with U.S. practice, and no new matter is added.

Attached hereto is a marked-up version of the changes made to the specification and claims by the current amendment. The attached page is captioned "Version With Markings to Show Changes Made."



Respectfully submitted,

Seed Intellectual Property Law Group PLLC

Robert Iannucci

Registration No. 33,514

RXI:peg

701 Fifth Avenue, Suite 6300 Seattle, Washington 98104-7092 (206) 622-4900; Fax: (206) 682-6031

VERSION WITH MARKINGS TO SHOW CHANGES MADE

In the Claims:

Claims 7 and 8 have been amended as follows:

- 7. (Amended) The method as claimed in any preceding claim_1, wherein said step of comparing first and second fields provides an output of the sum of a plurality of absolute pixel differences between respective said first and second fields, said absolute pixel differences exceeding a threshold value.
- 8. (Amended) A system for executing the method as claimed in any preceding claim 1.

09/914171

-1-

METHOD AND APPARATUS FOR INTERLACED/NON-INTERLACED FRAME DETERMINATION, REPEAT-FIELD IDENTIFICATION AND SCENE-CHANGE DETECTION

5 The present invention relates to methods and apparatus for the pre-processing of moving pictures before encoding. In particular, the present invention relates to methods and apparatus for determining whether a digital picture frame is an interlaced-scan picture or a noninterlaced-scan picture; identifying a repeated-field; and detecting a scene-change in a sequence of moving pictures.

10

Encoding methods such as the well known MPEG-1 and MPEG-2 standards have been popularly used for efficient transmission and storage of video. An MPEG encoder compresses an input video signal picture-by-picture to produce an output signal or bitstream compliant to the relevant MPEG standard. Pre-processing techniques can be applied to the 15 input video signal before encoding, for example, to remove noise and re-format the signal (eg. 4:2:2 to 4:2:0 conversion, image size conversion, etc.).

The input video signal is typically in an interlaced format, for example the 525/60 or 625/50 (lines/frequency) format, with each video frame consisting of two fields (top field and bottom 20 field). However, the source material of the video signal may be originally produced on film and converted to the video signal via a telecine process. This process converts a progressive source into an interlaced format and provides at the same time, if necessary, frame rate conversion for example using a 3:2 or 2:2 pulldown technique. In the case of 24 Hz film to 525/60 Hz video conversion, each progressive film picture is converted to two interlaced 25 video fields and, in addition, there are 12 repeated fields according to the 3:2 pulldown patterns in every second of the converted video. Improvement in coding efficiency can be obtained if the video source from film is identified and the repeated (or redundant) fields are detected and removed before coding. Pre-processing techniques applied before encoding can

also gain from the results of film picture detection.

The known methods of film mode detection can be widely classified into two categories: (1) film mode detection using film-frame pattern identification; and (2) film mode detection using automatic interlace/progressive frame detection.

5 The output of the type of method using film-frame pattern identification is a decision whether the input sequence is an interlaced video or a 3:2/2:2 pulldown film. The detection tries to identify the unique pattern of a 3:2 or 2:2 pulldown film. One of the most commonly used techniques is to detect the repeat field pattern in the 3:2 pulldown film (as described in US

patents 5,317,398 and 5,398,071). The pixel to pixel field differences between alternate fields

10 (fields with the same parity) are measured to identify whether the 3:2 repeat field pattern exists.

Another commonly used assumption is that the field differences between two interlaced fields is significantly greater than the field difference between two non-interlaced (or progressive)

15 fields. One method is to group the successive fields that have the least field differences as a film frame (as described in US patent 5,565,998). Another method is to measure the consecutive field differences of incoming fields and monitor the pattern to decide if it is an interlaced video, 3:2 film or 2:2 film (as described in US patents 5,365,273 and 5,689,301). In the above methods, the unique pattern is monitored for a period (typically spanning 5 to 20 64 fields) before a decision is made.

With the method of film mode detection using automatic interlace/progressive frame detection, apart from deciding whether an incoming sequence is a film, this type of detection also determines if a frame is interlaced or progressive and identifies a repeated field. Due to 25 the inclusion of the interlace/progressive detection for every frame, it does not have the slow response in interlace/progressive encoding as in the film-frame pattern identification methods described above. One of the methods used for the interlace/progressive detection, such as in US patent No. 5,452,011, is the intra-field and inter-field difference (IIFD) comparison. The IIFD method compares the inter-field and intra-field differences to detect whether two 30 consecutive fields are interlaced. The assumption is that the inter-field difference will be In most of the current video/film detection methods which have no automatic interlace/progressive detection, when there is a transition from interlaced video to film, the decision switching is made after a delay of a period typically spanning 5 to 64 fields. This means that the encoding of the film frames in this delay period is still done in interlace mode and redundant fields in this period are not removed before encoding. Similarly when there is a transition from film to interlaced video, the interlaced video frames in the decision switching delay period are still encoded as progressive frames.

10

A film sequence is often being edited, and a scene change may occur in any field. Sub-titles might also be added to any field of the film, thereby changing the 3:2 repeat-field pattern of the film so that the frames are not always progressive. Interlaced video sequences also consist of some progressive frames due to very little or no motion in between these fields. The current film detection methods which have no automatic interlace/progressive detection will not be able to detect these interlaced frames within a film and the progressive frames within the interlace video.

It is therefore an object of the present invention to address the above-mentioned problems by detecting whether a frame is interlace or progressive immediately after receiving the frame data so that the encoder can encode the frame as interlace or progressive according to the detection decision, or to at least provide a useful alternative.

For existing automatic interlace and progressive detection methods, which compare the intra-25 field and inter-field differences to make the detection decision, the comparison is not always accurate. The inaccuracy can be due to the inter-field difference being very small, because of little or no motion between successive frames, or to the intra-field difference being large because of very detailed texture or information within the field.

30 There are also inaccuracy problems in detection methods which assume that interlace

5

difference is significantly greater than progressive difference. The problem which arises from this assumption is that when the previous field (f_{N-1}) and current field (f_N) have little or no motion, the interlaced field difference between f_{N-1} and f_N might not be significantly greater than the difference between the progressive fields f_N and f_{N+1} .

The present invention is also intended to improve the accuracy of the interlace/progressive detection by making the detection decision which is not only based on the comparison between the interlace difference and the progressive difference, but also on the moving activities between successive frames. This is to check if an insignificant field difference between f_{N-1} and f_N is due to little motion, so as to avoid an incorrect decision due to the insignificant interlace difference.

The present invention provides a method of processing video data to detect field characteristics of the data, said data having a plurality of fields, including the steps of:

comparing first and second fields, said first field being a successive field of said second field;

comparing pixel values of respective sub-blocks of said first field and a third field, said second field being a successive field of said third field;

determining whether said first field is an interlaced field or a progressive field with 20 respect to a successive field of said first field based on said steps of comparing.

The present invention further provides an apparatus for processing video data to detect field characteristics of the data, said data having a plurality of fields, including:

first comparison means for comparing first and second fields, said first field being a successive field of said second field;

second comparison means for comparing pixel values of respective sub-blocks of said first field and a third field, said second field being a successive field of said third field;

progressive/interlace decision means for determining whether said first field is an interlaced field or a progressive field with respect to a successive field of said first field based on respective outputs of said first and second comparison means.

- 5 -

A preferred embodiment of the present invention is described hereinafter, by way of example only, with reference to the accompanying drawings, wherein:

Figure 1 is a block diagram of a system for determining interlace/non-interlace frames, identifying repeat fields and detecting scene-changes from a video source in a accordance with an embodiment of the present invention;

Figure 2 is a flow diagram illustrating the field grouping decision process;

Figure 3 is a block diagram of the consecutive field difference operation;

Figure 4 is a spatio-temporal pixel diagram illustrating the consecutive field difference computation;

Figure 5 is a flow diagram of the Interlace/progressive decision making algorithm;

Figure 6 is a spatio-temporal pixel diagram illustrating the moving region detection method.

In the preferred embodiment of the present invention, only two field memory units 101 and 15 102 are required. Referring to Figure 1, at a particular time, a video source 100 provides a field N to field memory 101, subtracter 103 and the consecutive field difference unit 106. At that time, the field memory 101 outputs the previous field N-1 to the second field memory 102 and to the consecutive field difference unit 106. Also at that time, the second field memory 102 outputs field N-2 to the subtracter 103. The sub-block sum of absolute 20 differences between the pixels of the incoming fields N and N-2 (functionally expressed as SBD (N-2,N), is measured using subtracter 103 and sub-block accumulator 104. The consecutive field difference between the current field N and the previous field N-1, (functionally expressed as CFD(N-1,N)), is measured by the consecutive field difference unit 106 and fed into an interlace/progressive decision unit 107. The value of SBD(N-2,N) is 25 used in a scene change decision unit 108 to decide if field N is a new scene compared to field N-2. It is also used in a repeat field decision unit 105 to decide if field N is a repeat field of field N-2. The number of sub-block moving pixels between field N-2 and N (functionally expressed as moving-pixel (N-2,N)), is computed by a sub-block moving pixel counter 109, and is input to the repeat filed decision unit 105 and the interlace/progressive decision unit 30 107. When field N+1 arrives, CFD(N,N+1) is then measured and compared with CFD(N-1) 1,N) in the interlace/progressive decision unit 107. The number of sub-block moving pixels, moving-pixel(N-1,N+1), is used in the interlace/progressive decision unit 107 to decide if fields N and N+1 are interlaced or progressive. The field grouping decision is made in a field grouping decision unit 110. The flow diagram relating to the field grouping decision unit 110 is shown in Figure 2. Fields N and N+1 are grouped as an interlaced or progressive frame depending on the output of the decision unit 107. If the current field N and field N+1 are detected as being interlaced by the unit 107, then fleds N and N+1 are grouped as an interlaced frame and field N+2 becomes the new current field. If fields N and N+1 are detected as being progressive, and fields N and N+2 are not detected as being repeated by unit 105, then fields N and N+1 are grouped as progressive and field N+2 becomes the new current field. However, if fields N and N+1 are detected as being progressive, and fields N and N+2 are detected as being progressive, and fields N and N+2 are detected as being repeated, then fields N and N+1 are gouped as being progressive, field N+2 is discarded and flied N+3 is set as the new current field.

15 Preferably, for all the sub-block measurements, each field is divided into 32 equal sub-blocks.

The block diagram of the consecutive field difference unit 106 is illustrated in figure 3. Subtractors 300 and 303 are used to compute the absolute pixel differences between fields N and N-1, and the smaller of the pixel differences is chosen by a comparator 301. The smaller pixel difference is then set to zero by noise attenuator 302 if it is less than a threshold T_{noise} , and each unattenuated pixel difference is accumulated in accumulator 305. This is illustrated in figure 4, where A is a pixel of the current field N and B and C are pixels from the previous field N-1 with vertical positions as shown. The pixel difference (PD) of pixel A is defined as the lesser of the absolute difference between A and B and the absolute difference between 25 A and C, ie.

$$PD = Min(|A - B|, |A - C|)$$

The PD of every pixel in field N is computed and the values of PD less than T_{noise} are regarded as noise and set to zero. The consecutive field difference CFD(N-1,N), of field f_{N-1} and field f_N , is defined as the sum of all the PDs in field f_N . The reason for selecting the

-7-

lesser of the two differences is that this will reduce inaccuracies in the calculation of the field differences arising from abnormal vertical displacement or horizontal edges. To decide whether field f_N and f_{N+1} are interlaced or progressive, the computation of the CFD(N-1,N) and CFD(N,N+1) is required.

5

The number of sub-block 'moving pixels' between fields f_{N-1} and f_{N+1} is also computed by the sub-block moving pixel counter 109 to find out if there is significant motion between fields f_{N-1} and f_{N+1} . The moving-pixel(N-1,N+1) is defined as the pixel in each sub-block (preferably 32 sub-blocks per field) between field f_{N-1} and f_{N+1} with pixel-to-pixel difference greater than 10 a threshold T_{move} .

A decision-making flow diagram is shown in figure 5. A ratio of CFD(N-1,N) to CFD(N,N+1) smaller than threshold T1 at step 403 indicates that fields f_N and f_{N+1} are interlaced, but to make sure that a small value of CFD(N-1,N) is not due to little or no 15 motion, it is also required that the number of moving pixels between field f_{N-1} and f_{N+1} is more than threshold T2 in step 405. The decision at steps 407 and 408, as to whether the fields N and N+1 are progressive, also depends on the CFD computed for the previous frame during the decision. Prev_CFD(N,N+1) is the 'CFD(N,N+1)' computed for the previous frame (equivalent to either CFD(N-2,N-1) if the field f_{N-1} is not a repeated field or CFD(N-20 3,N-2) if the field f_{N-1} is detected as a repeated field). The two thresholds T3 and T4 are used to set the sensitivity of decision switching from progressive-to-interlace and interlace-to-progressive respectively (at steps 409 and 410). This is to avoid the problem of an interlaced sequence which has little or no motion switching the decision too frequently between interlace and progressive. Suitable values for T_{notic} , T_{move} , T1, T2, T3 and T4 have been found to be 25 around 5, 30, 1.4, 100, 1.1 and 1.7 respectively.

If there is a scene change between f_{N-2} and f_N at step 401, then it may be meaningless to compare CFD(N-1,N) to CFD(N,N+1) as the scene change may occur between f_{N-1} and f_N , causing the value of CFD(N-1,N) to be arbitrary. The decision can only be based on the information in fields f_N and f_{N+1} . Therefore when there is a scene change detected (between

current field f_N and second previous field $f_{N,2}$), then the moving region detection (MRD) method is used at step 402. The MRD method detects any 'jagged region' or 'moving region' which is noticeable when two 'moving' consecutive fields are interlaced and viewed as a frame.

Referring now to figure 6 (which illustrates the MRD method), A and B are pixels from field N and C and D are pixels from field N+1 with vertical positions as shown. If the absolute difference between A and C, B and C, and B and D are all greater than a threshold $T_{lnterfaces}$ then the pair of pixels C and D are said to be 'interlaced pixels'. To decide whether the whole frame is interlaced, the detection is again preferably based on 32 sub-blocks. For each sub-block, if more than T_{region} number of the above 'interlaced pixels' are detected, then the block is considered to be interlaced. If more than one block is found interlaced, then the frame is considered as interlaced.

15 Repeat field detection is performed on a pair of fields of the same parity (odd or even). The field similarity measurement is again preferably based on 32 sub-blocks in which the absolute sum of all the pixel-to-pixel differences of each block is accumulated in the accumulator 104. The repeat-field decision unit 105 operates as follows: The pixel differences for each sub-block difference (SBD) are compared to a threshold T_{repeat} ie.,

20

$$SBD/(block_width \times block_height) < T_{repeat}$$

for all sub-blocks

If the pixel differences are smaller than T_{repeat} for all 32 of the sub-blocks, then a repeat field is said to be detected and can be skipped for encoding by the field grouping decision unit 110. It should be noted that the repeated field detection is performed only when the incoming frame is detected as progressive by the interlace/progressive detection.

To prevent an incorrect consecutive repeat field being detected due to very little motion, the following algorithm is implemented:

```
If ( curr_decision=repeat-field) && (prev_decision1 = repeat-field) && (prev_decision3=repeat-field) && (scene-change=No) )

then curr_decision=no-repeat-field

else if ( curr_decision=repeat-field) && (prev_decision1=repeat-field) && (moving-pixel > 35 in any one of the 32 sub-blocks) )

then curr_decision=no-repeat-field
```

where $prev_decision1$ is the first previous decision for repeat field detection and $prev_decision3$ is the third previous decision; scene-change is the scene change detection decision; and moving-pixel is the number of pixels with pixel difference greater than T_{move} computed in the sub-block moving pixel counter 109. A suitable value for T_{repeat} has been found to be around 2.5.

The differences between the current field and the previous field of the same parity are used to detect any significant change of scene. Making use of the sub-block difference (SBD), a simple thresholding method is employed by the scene change decision unit 108. Each block difference per pixel is compared with a threshold T_{scene} . If more than T_{block} of the sub-blocks has its difference per pixel greater than T_{scene} , then a scene change is detected, ie.

$$SBD/(block_width \times block_height) > T_{scene}$$
 for more than T_{block} sub-blocks

20 Apart from the above detection, a scene change is also detected by comparing the current field difference with the previous field difference to see if the current field difference has a sudden increment due to a scene change. The field difference (FD) is the sum of all the 32 absolute block differences. If the current field difference is more than T_{radioI} times greater than the previous field difference (prev_FD), then a scene change is said to be detected. The pseudocode of the scene change detection algorithm is as follows:

```
While (not end of sequence)
```

{

```
For i = 0 to 31,

{

If (SBD, I (block_widthxblock_height) > T_scene) then count = count + 1

FD = FD + SBD_1

}

If (count > T_block) then

scene-change is detected

Else If (FD/prev_FD > T_ratio1) then

scene-change is detected

If ((prev_scene_change = Yes) | | (prev_FD/FD < T_ratio2)) then

prev_FD = FD

FD = 0

Increment to next frame

}
```

In a 3:2 pulldown film sequence, subtitles may be added to a repeated field, resulting in the field not being detected as a repeat field. When this particular field becomes the current field, the current FD computed (between the current field N and second previous field N-2) will have a small value (because of the small change due to the subtitles). Therefore, in updating 20 the previous field difference ($prev_FD$), the condition ' $prev_FD/FD < T_{mio}$ ' is to avoid updating a 'repeat field difference' which will affect the scene change decision made later.

The prev_scene-change is a scene change decision of a previous frame. When there is a scene change detected in the previous frame, then the condition 'prev_FD/FD < T_{ratio2} ' might not be true due to the large value of prev-FD and hence the criteria 'prev_scene_change = Yes' will force an update of prev_FD. Suitable values for T_{scene} , T_{block} , T_{ratio1} and T_{rado2} have been found to be about 15, 25, 2.5 and 3.0 respectively.

An advantage of embodiments of the present invention is to make accurate decisions as to 30 whether a frame should be encoded as an interlace or progressive frame immediately after the -11-

second field of the frame is received. This enables the MPEG encoder to encode the frame as interlace or progressive accordingly accurately, including those odd interlaced frames within a film sequence due to editing or the odd progressive frames within an interlaced video sequence. In the above-described interlace/progressive determination method, apart from comparing the consecutive field differences, the moving activities between two successive frames is also computed to ensure that interlaced fields with little or no motion will not cause an incorrect decision. The present invention also addresses the situation where the scene change occurs in the current frame. The moving region detection method is then used for the interlace/progressive determination.

10

15

15

30

- 12 -

Claims:

- 1. A method of processing video data to detect field characteristics of the data, said data having a plurality of fields, including the steps of:
- comparing first and second fields, said first field being a successive field of said second field;

comparing pixel values of respective sub-blocks of said first field and a third field, said second field being a successive field of said third field;

determining whether said first field is an interlaced field or a progressive field with respect to a successive field of said first field based on said steps of comparing.

- 2. The method as claimed in claim 1, further including the step of accumulating, in an accumulator means, absolute differences between the pixel values of said first and third fields.
- 3. The method as claimed in claim 2, wherein said step of determining is further based on an output of said accumulator means.
- 4. The method as claimed in claim 2, further including the step of determining whether said first field is a repeated field based on a result of said step of comparing pixel values, on said output of said accumulator means and on a result of said step of determining whether said first field is an interlaced field or a progressive field.
- 5. The method as claimed in claims 3 or 4, further including the step of determining whether or not there has been a scene change between said first and third fields, at least in part based on said output of said accumulator means.
 - 6. The method as claimed in claim 5, further including the step of grouping successive fields according to one or more of said steps of determining.
 - 7. The method as claimed in any preceding claim, wherein said step of comparing first

and second fields provides an output of the sum of a plurality of absolute pixel differences between respective said first and second fields, said absolute pixel differences exceeding a threshold value.

- 5 8. A system for executing the method as claimed in any preceding claim.
 - 9. Apparatus for processing video data to detect field characteristics of the data, said data having a plurality of fields, including:

first comparison means for comparing first and second fields, said first field being a successive field of said second field;

second comparison means for comparing pixel values of respective sub-blocks of said first field and a third field, said second field being a successive field of said third field;

progressive/interlace decision means for determining whether said first field is an interlaced field or a progressive field with respect to a successive field of said first field based on respective outputs of said first and second comparison means.

- 10. The apparatus as claimed in claim 9, further including accumulator means for accumulating absolute differences between the pixel values of said first and third fields.
- 20 11. The apparatus as claimed in claim 10, wherein the determining of whether said first field is an interlaced field or a progressive field is further based on an output of said accumulator means.
- 12. The apparatus as claimed in claim 11, further including repeat field decision means for determining whether said first field is a repeated field based on said output of said second comparison means, said output of said accumulator means and on an output of said progressive/interlace decision means.
- 13. The apparatus as claimed in claims 11 or 12, further including scene change decision30 means for determining whether or not there has been a scene change between said first and

The state of the s

third fields, at least in part based on said output of said accumulator means.

14. The apparatus as claimed in claim 13, further including field grouping decision means for grouping successive fields according to one or more of said scene change decision means,
5 repeat field decision means or interlace/progressive decision means.

PCT/SG99/00014

1/6




Figure 1




Figure 2





Figure 3







Figure 5



DECLARATION AND POWER OF ATTORNEY

As the below-named inventors, we declare that:

Our residences, post office addresses, and citizenships are as stated below under our names.

We believe we are the original, first, and joint inventors of the invention entitled "METHOD AND APPARATUS FOR INTERLACED/NON-INTERLACED FRAME DETERMINATION, REPEAT-FIELD IDENTIFICATION AND SCENE-CHANGE DETECTION," which is described and claimed in the specification and claims of International Patent Application No. PCT/SG99/00014, which was filed on 26 February 1999 and for which a patent is sought.

We have reviewed and understand the contents of the foregoing specification, including the claims, as amended by any amendment specifically referred to herein (if any).

We acknowledge our duty to disclose information of which we are aware which is material to the patentability and examination of this application in accordance with 37 C.F.R. § 1.56(a).

We hereby claim foreign priority benefits under 35 U.S.C. § 119 of the foreign patent application listed below:

PRIOR FOREIGN/PCT APPLICATION(S) AND ANY PRIORITY CLAIMS UNDER 35 U.S.C. 119:						
COUNTRY	APPLICATION NUMBER	DATE OF FILING	PRIORITY CLAIMED UNDER 35 USC 119			
PCT	PCT/SG99/00014	26 February 1999	Yes			

I hereby appoint George C. Rondeau, Jr., Reg. No. 28,893; David H. Deits, Reg. No. 28,066; William O. Ferron, Jr., Reg. No. 30,633; Richard G. Sharkey, Reg. No. 32,629; David V. Carlson, Reg. No. 31,153; Karl R. Hermanns, Reg. No. 33,507; Michael J. Donohue, Reg. No. 35,859; Jane E. R. Potter, Reg. No. 33,332; Robert Iannucci, Reg. No. 33,514; Lorraine Linford, Reg. No. 35,939; David W. Parker, Reg. No. 37,414; E. Russell Tarleton, Reg. No. 31,800; Ellen M. Bierman, Reg. No. 38,079; Brian G. Bodine, Reg. No. 40,520; Robert M. Ward, Reg. No. 26,517; Frank Abramonte, Reg. No. 38,066; Kevin S. Costanza, Reg. No. 37,801; Stephen J. Rosenman, Reg. No. 43,058; Brian L. Johnson, Reg. No. 40,033; Susan D. Betcher, Reg. No. 43,498; William T. Christiansen, Reg. No. 44,614; Jeffrey C. Pepe, Reg. No. 46,985; Timothy L. Boller, Reg. No. 47,435; James M. Verna, Reg. No. 33,287; James A. Mesher, Reg. No. P-48,700; Mae J. Rosok, Reg. No. P-48,903; Dale R. Cook,

ں ں

67

Reg. No. 42,434; comprising the firm of Seed Intellectual Property Law Group PLLC, 701 Fifth Avenue, Suite 6300, Seattle, Washington 98104-7092, as my attorneys to prosecute this application and transact all business in the Patent and Trademark Office connected therewith. Please direct all telephone calls to **David V. Carlson**, at (206) 622-4900 and telecopies to (206) 682-6031.

We further declare that all statements made herein of our own knowledge are true and that all statements made on information and belief are believed to be true; and further, that these statements were made with the knowledge that the making of willfully false statements and the like is punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code, and may jeopardize the validity of any patent issuing from this patent application.

J.	u/dy	hi	
Yau Wei Lucas	Hui U		
Date			_
Residence	:	City of Singapore	000
		Country of Singapore	Jap
Citizenship	:	Singapore	-
P.O. Address	:	10H Braddell Hill, #24-31	
		Singapore 579727	

Kwong Huang Goh

Date 31 0ct 2001

Residence

City of Singapore

Country of Singapore $SC_{1}P$

Citizenship

Singapore

P.O. Address

Block 323 Jurong East Street 31, #06-216

Singapore 600323